

LOC I-CDW	APP CRS	Rwy Idg	4418
109.35	223°	THRE	172
		Apt Elev	172


LOC RWY 22

CALDWELL / ESSEX COUNTY (CDW)

NA Circling to Rwy 4, 10, 28 NA at night. When VGSI inop, Straight-in/Circling Rwy 22 procedure NA at night. Visibility reduction by helicopters NA. When local altimeter setting not received, use Newark altimeter setting and increase all MDA 60 feet and Circling Cats A and C visibility 1/4 mile. KOLLI INT minimums: increase all MDA 60 feet and increase S-22 Cats C/D and Circling Cats A/B/C visibility 1/4 mile.


MISSED APPROACH: Climb to 1100 then climbing right turn to 2700 on I-CDW NE course to FAAIR INT and hold, continue climb-in-hold to 2700.

ATIS	NEW YORK APP CON	CALDWELL TOWER ★	GND CON	CLNC DEL	UNICOM
135.5	127.6 379.9	119.8 (CTAF) 0	121.9	121.1	122.95



NE-2, 17 OCT 2013 to 14 NOV 2013

NE-2, 17 OCT 2013 to 14 NOV 2013



CATEGORY	A	B	C	D
S-22	960-1 788 (800-1)	960-1¼ 788 (800-1¼)	960-2½ 788 (800-2½)	1100-3 928 (1000-3)
CIRCLING	960-1 788 (800-1)	980-1¼ 808 (900-1¼)	1040-2½ 868 (900-2½)	1100-3 928 (1000-3)
KOLLI INT MINIMUMS				
S-22	560-1	388 (400-1)	560-1½	388 (400-1½)
CIRCLING	940-1 768 (800-1)	980-1 808 (900-1)	1040-2½ 868 (900-2½)	1100-3 928 (1000-3)

FAF to MAP 5.3 NM

Knots	60	90	120	150	180
Min:Sec	5:18	3:32	2:39	2:07	1:46